

JPEG2000 16CH Bank DVR

DVR-H13P-NT, DVR-H13N-NT



For : Bank, Military, Hospital, Government,
Post office...Where need long time recording

10HDDs Capacit
Long time recoding

Features

- JPEG2000 Algorithm compression
- Support 10HDDs, 5000G above
- 480(400)fps recording capability
- Triplex (Playback / Recording / Ethernet)
- Multi Language OSD
- IR Remote Controller
- Spot monitor output
- USB (Device) port for firmware upgrade
- Easy PTZ camera control by front panel buttons
- Remote viewer in good picture quality through TCP/IP
- VGA output (Supporting TFT LCD Monitor)
- Support DDNS (Dynamic Domain Name Server)
- Network transmission speed adjustable (Scalability)
- Support Central monitoring system (CMS)



Specifications

MODEL NUMBER		N-BANK16-DVR
Compression	JPEG2000 Algorithm	
Storage Capacity	10 HDDs	
VGA	1CH (Supporting TFT LCD Monitor)	
Video Input	16CH	
Video Output	Monitor / Spot Monitor	
Audio	Input: 4CH audio input , Output:1CH audio output	
Split Screen	1,4,6,8,9,13,16 split	
Compressed Rated	Low, Mid, High, Super, Hyper	
Recording Speed	NTSC	120fps(Full),240fps(Dual),480fps(Quad)
	PAL	100fps(Full),200fps(Dual),400fps(Quad)
Recording Resolution	Full (720x240 / 720x288), Dual(360x240/ 360x288), Quad (360x120 / 360x144)	
Display	Real time for all channel	
Simplex/Duplex/Triplex	Triplex (Playback / Recording / Ethernet)	
Zoom	Available	
PIP	Available	
Motion Detect	Area division : 16x12	
Recording Mode	Time, Motion, Schedule, Alarm, Emergency	
Search Mode	Percentage Search, Date/ Time Search, Event Search	
Password Protection	Admin, Manager, User1~8 Allowed to access the system	
Alarm Input	16 Alarm (NO/NC)	
Relay Output	1 (NO/NC)	
Backup	Download via IP Network, VCR, DVD-RW back-up,	
IR Remote Controller	Built-in	
Network (TCP/IP)	Remote Software(Remote live view ,playback, and save as AVI), IE(Remote live view, backup, and save backup to AVI), Two users access is available, Transmission speed adjustable	
CMS	Available	
Firmware upgrade	USB port for firmware upgrade	
Operation Temperature	41°F~104°F (5°C~40°C)	
Operation Humidity	Less than 90%	
Dimension	440mm(W) x 535mm(D) x 175mm(H)	
Weight (N.W)	Approx 15 kgs (w/o HDD)	
Power Supply	500W	

specifications and appearance are subject to change without notice