

Super Hi-Res. Color Dome Camera

S-MTC2438HQ-D, S-MTC2438HQDN-D, S-MTC2438H-D, S-MTC2338-D

S-MTC2438HQ-D, S-MTC2438HQDN-D Features

- 1/3" Super Hi-Res. Dome Camera
- SONY HQ1/540TVL/0.25Lux@F1.2
- Built-in Aspherical Lens
- AES/AGC/BLC/FL Switchable(ON/OFF)
- Color mode switches to B/W Mode(MTC-2438HQDN Only)

S-MTC2438H-D Features

- 1/3" Hi-Res. Dome Camera
- 480TVL/ 0.3Lux@F1.2
- Built-in Aspherical Lens
- AES/AGC/BLC/FL Switchable(ON/OFF)

S-MTC2338-D Features

- 1/3" Med-Res. Dome Camera
- 420TVL/ 0.15Lux@F1.2
- AES/AGC/BLC/FL Switchable(ON/OFF)
- Built-in Aspherical Lens

Option:



MTB-201



Wall Mount



Attach Ceiling Top Plate



S-MTC2438H-D, S-MTC2438HQDN-D



S-MTC2438H-D

S-MTC2338-D

Specifications

	S-MTC2438HQ-D,S-MTC2438HQDN-D		S-MTC2438H-D		S-MTC2338-D	
	PAL	NTSC	PAL	NTSC	PAL	NTSC
TV System	PAL	NTSC	PAL	NTSC	PAL	NTSC
Image Sensor	1/3" SONY Color CCD					
Number of Total Pixels	795(H)X596(V)	811(H)X508(V)	795(H)X596(V)	811(H)X508(V)	537(H)X597(V)	537(H)X505(V)
Synchronizing System	Internal					
Resolution	540 TVL		480 TVL		420 TVL	
Minimum Illumination	0.25 Lux@F1.2 Color mode automatically switches to B/W mode under 2 Lux (MTC-2438HQDN Only)		0.3 Lux@F1.2		0.15 Lux@F1.2	
Signal to Noise Ratio	More Than 50 dB(AGC Off)				More Than 48 dB(AGC Off)	
Automatic Gain Control	ON/OFF (Switchable)					
F.L. (Flickerless)	ON/OFF (Switchable)					
AES	ON/OFF (Switchable)					
Back Light Compensation	ON/OFF (Switchable)					
DC Level	The VR for adjusting the IRIS level of auto Iris lens.					
White Balance	AWB		2500°K~9200 °K			
Video Output	1Vp-p Composite / 75 Ω					
Lens/Angle of view(H)	Standard:f2.9mm~10mm/F1.2 Aspherical Auto Iris Lens / 94.6 °~28.8 ° Option:f2.5mm~6.0mm/F1.3 Aspherical Auto Iris Lens / 108.2 ~47.6 ° Option:f9mm~22.0mm/F2.0 Auto Iris Lens / 29.2 ~13.0 °					
Power Supply	Standard:12 Vdc; Option:12 Vdc/24 Vac					
Power Consumption	2.0 W		1.6 W		1.8 W	
Operation Temperature	-10°C~+50 °C					
Operation Humidity	RH85% or less					
Storage Temperature	-20°~60 °C					
Dimensions	118(DIA) X 88(H) mm					
Weight	12 Vdc: 300 g; 12 Vdc/24 Vac: 370 g					

specifications and appearance are subject to change without notice

Dimensions

UNT:mm Tol:±0.5

