

# HQ1 Color Dome Camera

Black or Ivory Finish Available

S-MTC808HQ-D, S-MTC808H-D, S-MTC805-D



## S-MTC808HQ-D

### Features

- 1/3" Super Hi-Res.
- Color Dome Camera
- SONY HQ1/ 540TVL/ 0.5Lux@F2.0

## S-MTC805-D

### Features

- 1/3" Med-Res.
- Color Dome Camera
- 420TVL/ 0.3Lux@F2.0

## S-MTC808H-D

### Features

- 1/3" Hi-Res.
- Color Dome Camera
- 480TVL/ 0.35Lux@F2.0



## Specifications

	S-MTC808HQ-D		S-MTC808H-D		S-MTC805-D	
	PAL	NTSC	PAL	NTSC	PAL	NTSC
TV System	PAL	NTSC	PAL	NTSC	PAL	NTSC
Image Sensor	1/3" SONY SUPER HAD CCD					
Number of Total Pixels	795(H)x596(V)	811(H)x508(V)	795(H)x596(V)	811(H)x508(V)	537(H)x597(V)	537(H)x505(V)
Resolution ; DSP	540TVL ; SONY HQ1		480TVL		420TVL	
Minimum Illumination	0.5Lux@F2.0		0.35Lux@F2.0		0.3Lux@F2.0	
Video Output ; Connector	1.0Vp-p Composite, 75 Ω, BNC					
Signal to Noise Ratio	More than 50dB					
Gamma Correction	0.45					
Synchronizing System	Internal					
Automatic Electronic Shutter	Automatic, 1/50(60)sec.~1/100,000sec.					
Automatic Gain Control	Automatic					
Automatic White Balance	Automatic					
Back Light Compensation	NA		NA		Automatic	
Flickerless	NA					
Digital Day&Night Mode	NA					
Mirror Mode	NA					
Automatic IRIS	NA					
Adjustment VR	NA					
Lens Mount	Built-in Board Lens					
Lens, Angle of View(H)	Standard:f3.6mm/F2.0/72.5 ° Options:f2.5mm/105 °, f2.9mm/90 °, f6.0mm/47.5 °, f8.0mm/36.5 °, f12.0mm/24.5 °					
Power Supply ; Consumption	12Vdc ; 1.5W		12Vdc ; 1.3W		12Vdc ; 1.0W(83mA)	
Operation ; Storage Temp.	-10°C~50 °C ; -20°C~60 °C					
Operation ; Storage Humidity	Maximum:RH80% ; RH90%					
Dimensions	112(DIA)x70(H)mm					
Net Weight	220g					
Accessories Series Option(Page)	NA					

specifications and appearance are subject to change without notice

## Dimensions

UNT:mm Tol:±0.5

