

Wireless Color Baby Monitor



Features

- TFT LCD brings ultra-high resolution and high brightness images.
- Voice-activated video transmission.
- Built-in microphone in camera for audio monitoring.
- Low battery power indicator in monitor.
- Built-in infrared LEDs provide images in the darkness .
- The two-piece design camera offers flexible adjustment of rotating angle and keeps the lens steady.
- Both monitor and camera are battery or AC adapter operated.
- Both monitor and camera can be free standing or wall mounted.
- 2.4 GHz signal penetrates walls, floors, and ceilings (range of approximately 300 feet with a clear line of sight).

Specifications

Camera

Frequency	2.4 GHz
Antenna	Built-in omni-directional antenna
Channel	4 selectable channels
A/V Mod/Demod. Method	FM
Image Sensor	CMOS image sensor
Effective pixels	366 (H) x 288 (V)
Lens	f 6.0mm, F2.0
S/N Ratio	>48dB
Microphone	Built-in
Infrared LED	6 pcs
Dimensions	7.7 (W) x 12.8 (H) x 5 (D) cm (3 x 5 x 1.9 inches)
Weight	115 g without batteries
Power	DC 6V, 300mA or 4AA-size batteries
Operating temperature	0 C ~ 40 C (32 F ~ 104 F)

Monitor

Frequency	2.4 GHz
Antennas	Built-in omni-directional antenna
Channel	4 selectable channels
A/V mod/Demod. method	FM
Display	2.36" LTPS-TFT LCD
Resolution	480X234(115,200 pixels)
Brightness	240 cd/m
Display colors	Full-color
Dimensions	6.7(W) x 13.5(H) x 4.1(D) cm (2.6 x 5.3 x 1.6 inches)
Weight	130g without batteries
Power	DC 6V, 1A or 4 AA-size batteries
Operating temperature	0 ~ 40 (32 ~ 104)
	Specifications are subject to change without notice

specifications and appearance are subject to change without notice