

Wireless Color Baby Monitor



Features

- TFT LCD brings ultra-high resolution and high brightness images
- Voice-activated video transmission.
- Built-in microphone in camera for audio monitoring.
- Low battery power indicator in monitor.
- Built-in infrared LEDs provide images in the darkness.
- The two-piece design camera offers flexible adjustment of rotating angle and keeps the lens steady.
- Both monitor and camera are battery or AC adapter operated.
- Both monitor and camera can be free standing or wall mounted.
- 2.4 GHz signal penetrates walls, floors, and ceilings (range of approximately 300 feet with a clear line of sight).

Specifications

CAMERA

Frequency	2.4 GHz
Antennas	Built-in omni-directional antenna
Channel	4 selectable channels
A/V mod/demod. method	FM
Image sensor	CMOS image sensor
Effective pixels	NTSC 366(H) x 288 (V)
Lens	f 3.7mm, F2.8
S/N Ratio	>48dB
Microphone	Built-in
Infrared LED	6 pcs
Dimensions	7.7(W)x 12.8(H) x 5(D) cm
Weight	115g without batteries
Power	DV 6V, 400 mA or 4AA-size batteries
Operating temperature	0°C ~ 40°C (32°F ~ 104°F)

MONITOR

Frequency	2.4 GHz
Antennas	Built-in omni-directional antenna
Channel	4 selectable channels
A/V mod/demod. method	FM
Display	2.36"LTIPS-TFTLCD
Brightness	240 cd/ m ³
Display colors	Full-color
Connection terminals	AV output jack
Dimensions	6.7(W) x 13.5(H) x 4.1(D)cm
Weight	130g without batteries
Power	DC 6V, 1A or3AA-size batteries
Operating temperature	0°C ~ 40°C (32°F ~ 104°F)

specifications and appearance are subject to change without notice