

Digital Wireless Child Tracker



Features

- Keep an eye on your children playing in garden, playground or even in shopping mall.
- Both units can communicate at over 50m in an open-air environment.
- LEDs to guide the parent to the child instantly.
- Each parent unit is capable of monitoring 4 separate child units.
- When the Parent unit is getting closer to the Child unit, the LEDs will be flashing quicker and the beep sound will become quicker.
- Setting warning range - You can set distance between Child Unit and Parent Unit (Near range / Normal range / Far range).
- The user can use the Child unit to call the Parent unit actively.
- Low power detection - When the battery power is low, the powerLED will flash red as a warning.

Specifications

System

Operating Range :	Typical 50 meters light of sight
Warning Range:	5 to 30 meters § §

Parent Unit

Power Supply:	2 x AAA 1.5V non rechargeable alkaline batteries
Dimension:	W:45mm H:115mm D:32mm
Weight:	50g
Operating temperature:	0°C ~ 40°C (32°F ~ 104°F)

Child Unit

Power Supply:	1 x AC power adapter DC 6V 200 mA 1 x LIR2450 Li+ 3.6V rechargeable battery
Dimension:	W:45mm H:45mm D:20mm
Weight:	34g
Operating temperature:	0°C ~ 40°C (32°F ~ 104°F)

specifications and appearance are subject to change without notice