

15M Low Power Consumption IR Camera

MR-C21PD-NT, MR-C21ND-NT, MR-C28PD, MR-C28ND-NT

Features

- CAT's EYE LED x 6 pcs (15M) / CAT's EYE LED x 12pcs (30M)
- View angle: 80°; Beam spread: 30 ~30°/per LED
- IR Status: under 10 Lux by CDS auto control
- More than 20,000 hours of LED life
- IP 66 housing



NT-IR15 SERIES



NT-IR30 SERIES

~ Special structural design for heater eliminating Lower power consumption~

Specifications

Model Number	N-TIR15-T	N-TIR30-T
IR Distance	15 meters	30 meters
IR LED	CAT'S EYE LED x 6pcs	CAT'S EYE LED x 12pcs
IR View Angle	View angle: 80°, Beam spread: 20° ~ 30°/per LED	
IR Wavelength	850nm	
IR Status	Under 10 Lux by CDS auto control	
LED life	More than 20,000 Hours	
Protection Class	IP 66	
Power Requirement	12V DC	
Power Consumption	IR on: 280mA	IR on: 550mA
Construction	Aluminum with sunshield weatherproof	
Operation Temp.	Operating: -10°C ~ +55°C , Storage: -30°C ~ +80°C	
Dimensions	128mm(W) x60mm (H)	250mm(W) x95mm (H)
Weight	431g	927g
Dimension		
NT-IR15 Series		
NT-IR30 Series		

specifications and appearance are subject to change without notice