

25M IR Covert Front Cover Camera (DNR)

HR-C18PD-NT, HR-C18ND-NT, HR-C19PD-NT, HR-C19ND-NT



Features

- Camera lens covered by the special patented front cover
- Easy adjustable view angle
- Built-in DNR (Digital Noise Reduction)
- 1/3" color CCD sensor for clear video output



Specifications

Model Number		N-CCMS2S11-IR	N-CCHS2S11-IR
Scanning System	NTSC	525 lines 2:1 interlace	
	PAL	625 lines 2:1 interlace	
Scanning Frequency	NTSC	15,734Hz(H) , 60Hz(V)	
	PAL	15,625Hz(H) , 50Hz(V)	
Effective Pixels	NTSC	512(H) x 492(V)	768 (H) x 492(V)
	PAL	512(H) x 582(V)	752 (H) x 582(V)
Electronic Shutter	NTSC	1/60-100,000sec.	
	PAL	1/50-100,000sec	
Image Device	1/3" SONY Super HAD CCD		
Horizontal Resolution	480 TV lines Enhanced	560 TV lines Enhanced	
Sensitivity	0.01Lux, 0 Lux at IR on		
Signal to Noise	More than 52dB		
Gain Control	Auto + 18dB Max		
White Balance	Auto ATW 2500-9500 ° K		
Sense-UP times	Max 32 times		
DNR	Built-in DNR (Digital Noise Reduction)		
BLC	Auto		
Gamma Correction	0.45		
SYNC System	Internal		
Lens/Focus point	4.3mm (Optional 6mm)		
Video Output	1.0 Vp-p, 75 Ohm		
IR LED	49 units 940nm infrared LED		
IR Distance	25~30 meters (Subject to IR reflection conditions)		
IR Status	IR on: Under 10 Lux, by PT auto control		
LED life	More than 10,000 Hours		
Protection Class	-		
Power Requirement (± 10%)	DC12V, 1mA		
Power Consumption (± 10%)	IR on: 480mA, IR off: 80mA		
Operation Temp.	Operating: -10 ~ + 55 °C , Storage: -30 ~ + 70 °C , Humidity:0~95%RH		
Dimensions (mm)	Main body:280(H) x 230(W), Bracket:195(H) x 100(W) x 71(D)		
Weight (N.W)	1.1kg		
Design and specifications are subject to change without notice.			

