

Super High Res. Color Mini Camera

S-MTC832HQ-M, S-MTC832H-M



S-MTC832HQ-M Features

- 1/3" Super Hi-Res. Color Camera
- SONY Super HAD CCD
- SONY HQ1/ 540TVL/ 0.15Lux@F1.0
- AES/AGC/BLC/F.L.(ON/OFF)
- Video/DC Iris Control

S-MTC832H-M Features

- 1/3" Hi-Res. Color Camera
- SONY Super HAD CCD
- 480TVL/ 0.2Lux@F1.0
- AES/AGC/BLC/F.L.(ON/OFF)
- Video/DC Iris Control

S-MTC832HQ-M



S-MTC832H-M





Specifications


	S-MTC832HQ-M		S-MTC832H-M	
TV System	PAL	NTSC	PAL	NTSC
Image Sensor	1/3" SONY SUPER HAD CCD			
Number of Total Pixels	795(H)x596(V)	811(H)x508(V)	795(H)x596(V)	811(H)x508(V)
Resolution ; DSP	540TVL ; SONY HQ1		480TVL	
Minimum Illumination	0.15Lux@F1.0		0.2Lux@F1.0	
Video Output ; Connector	1.0Vp-p Composite, 75 Ω ; BNC			
Signal to Noise Ratio	More than 50dB (AGC Off)			
Gamma Correction	0.45			
Synchronizing System	Internal			
Automatic Electronic Shutter	ON:1/50(60)sec.~1/100,000sec. / OFF:1/50(60)sec.			
Automatic Gain Control	ON / OFF			
Automatic White Balance	Automatic			
Back Light Compensation	ON / OFF			
Flickerless	ON / OFF			
Digital Day&Night Mode	NA			
Mirror Mode	NA			
Automatic IRIS ; Connector	VIDEO / DC ; D4 IRIS Jack			
Adjustment VR	DC Level			
Lens Mount	C / CS mount (With Adaptor)			
Lens, Angle of View(H)	Lens Option: Please See the Page of Lens Series			
Power Supply ; Consumption	12Vdc ; 2.0W		12Vdc ; 1.6W	
Operation ; Storage Temp.	-10°C~50 °C ; -20°C~60 °C			
Operation ; Storage Humidity	Maximum:RH80% ; RH90%			
Dimensions	55(W)x47(H)x55(D)mm			
Net Weight	200g			
Accessories Series Option(Page)	Bracket:MTB-109(G-3) ; Housing(G-4)			

Dimensions

UNT:mm Tol:±0.5



12Vdc



specifications and appearance are subject to change without notice