

## Vandalproof Camera for Vehicle

S-MTCL405DHQ-R, S-MTCL405D-R

## S-MTCL405DHQ-R Features

- 1/3" Super Hi-Res.
- SONY HQ1/ 540TVL/ 0.4Lux@F2.0
- IR LEDs on at 1Lux
- Build in 12 IR LEDs
- Illuminating Distance to 15 m
- Vandalproof Design
- De-vibration Mechanism for Vehicle Use

Option:



MTB-402



Wall Mount

De-vibration Design



## S-MTCL405D-R Features

- 1/3" Med-Res.
- 420TVL/ 0.4Lux@F2.0
- IR LEDs on at 1Lux
- Build in 12 IR LEDs
- Illuminating Distance to 15 m
- Vandalproof Design
- De-vibration Mechanism for Vehicle Use

## Specifications

	S-MTCL405DHQ-R		S-MTCL405D-R	
	PAL	NTSC	PAL	NTSC
TV System	PAL	NTSC	PAL	NTSC
Image Sensor	1/3" SONY COLOR CCD			
Number of Total Pixels	795(H)x596(V)	811(H)x508(V)	537(H)x597(V)	537(H)x505(V)
Resolution ; DSP	540TVL ; SONY HQ1		420TVL	
Minimum Illumination	0Lux			
Video Output ; Connector	1.0Vp-p Composite, 75Ω ; BNC			
Signal to Noise Ratio	More than 48dB			
Gamma Correction	0.45			
Mechanical IR Cut Filter	NA			
IR LED ; Working Distance	12 units (IR LEDs on<1Lux, IR LEDs off>5Lux) ; Outdoor:15m			
Synchronizing System	Internal			
Automatic Electronic Shutter	Automatic, 1/50(60)sec.~1/100,000sec.			
Automatic Gain Control	Automatic			
Automatic White Balance	Automatic			
Back Light Compensation	NA		Automatic	
Flickerless	NA			
Digital Day&Night Mode	NA			
Mirror Mode	NA			
Automatic IRIS	NA			
Adjustment VR	NA			
Lens Mount	Built-in Board Lens			
Lens, Angle of View(H)	Standard:4.3mm/F2.0 Options:6.0mm/8.0mm/12mm F2.0			
Water Resistance	IP65			
Max. Breaking Strength	10 pound			
Power Supply ; Consumption	12Vdc,12Vdc/24Vdc ; IR on:3.4W(280mA); IR off:1.7W(140mA)		12Vdc,12Vdc/24Vdc ; IR on:2.8W(230mA); IR off:1.2W(100mA)	
Operation ; Storage Temp.	-10°C~50 °C ; -20 °C~60 °C			
Operation ; Storage Humidity	Maximum:RH80% ; RH90%			
Dimensions	108(DIA)x77(H)mm			
Net Weight	420g			
Accessories Series Option(Page)	Wall Bracket:MTB-402			

specifications and appearance are subject to change without notice

## Dimensions

UNT:mm Tol:±0.5

